

THINKCENTRE

Edge62z

TECHSPECS



Product Name	ThinkCentre Edge 62z	Slots & Connectors	
Form Factor	All-in-One	2.5" Internal Bay	1 (HDD)
Operating System	Genuine Windows® 7 Professional 32/64bit Genuine Windows® 7 Home Premium 32/64bit Genuine Windows® 7 Home Basic 32/64bit	5.25" Internal Bay Mini PCI-E SATA	1 (Slim ODD) ³ 1 (for Wi-Fi module) ³ 2
		I/O Ports (Side)	
Chipset	Intel® H61	USB (Type)	2 x USB 2.0
Processor	Intel® Core™ i3-3220/3240 (3rd generation) Intel® Core™ i3-2120/2130 (2nd generation) Intel® Pentium™ G2120 (3rd generation) Intel® Pentium™ G630/G640/G645/G850/G860/G870 (2nd generation) Intel® Celeron™ G460/G465/G530/G540/G550/G555 (2nd generation)	Microphone Headphone	1 1
		I/O Ports (Rear)	
Memory		USB (Type) Display (Input)	4 x USB 2.0 N/A
DIMM Slots	1	Display (Output)	N/A
Type	DDR3 (SoDIMM)	COM	1
Speed	1600 MHZ	PS/2	N/A
Module Type Supported	2GB/4GB/8GB	LAN (RJ45)	1
Max Memory	8GB	DC-IN	1
Graphics		Security	
Integrated	Intel® HD Graphics	Security Platform Chip	N/A
Discrete	N/A	Computrace	N/A
Displays		USB Disable	Yes
Panel Size	18.5" Wide	Physical Security	Kensington Slot Support
Multi-touch	N/A	Tool-less Features	
Backlight Type	LCD	Chassis	N/A
Aspect Ratio	Wide (16:9)	HDD	N/A
Resolution	1366 x 768	ODD	N/A
Peripherals		Memory	N/A
Keyboard	Lenovo® Ultra Slim Plus Wireless Keyboard Lenovo® Preferred Pro Full-size Keyboard (USB) Lenovo® Slim New F5 USB Keyboard	Power Supply	External 120W 87% Auto-sensing
Mouse	Ultra Slim Plus Wireless Mouse Enhanced Optical USB Mouse	Chassis Dimension ⁶	
Web Camera ³	1 Mega Pixel Webcam	Height (mm)	469.7
Microphone	Optional	Width (mm)	368.3
Speaker	Integrated 2W x 2	Depth (mm)	59.5
Hard Drive		Weight (kg) ⁷	5
Supported Types	Serial-ATA, SATA-II	Environment Attributes	
Bus Transfer Rate	3 Gb/s	Temperature	Operating: 10°C - 35°C (50F to 95F) Non-operating: -20°C - 60°C (with package) Wet Bulb Temperature: 25°C (max) (Operating)
Available Drives	2.5" 7200rpm 320GB/500GB 2.5" 5400rpm 320GB/500GB/1TB ⁴	Relative Humidity	Operating: 20% ~ 80% (non-condensing) Non-Operating: 20% ~ 80% (non-condensing)
Optical Drive		Max Vibration	Operating: 0.27 G at 5 to 500 Hz at 0.5 octave/min, Random Non-Operating: 1.04 G at 2 to 200 Hz at 1 octave/min With Package: 1.04 G at 2 to 200 Hz at 1 octave/min
Supported Types	Serial-ATA	Max Shock	Operating: Bottom half-sine pulse with a change in velocity of 37.4 cm/sec (14.7 inches/sec) Non-Operating: 45-G faired square wave with a velocity change of 441 cm/sec (173.7 inches/sec)
Available Drives	Slim DVD-ROM/Slim DVD Recordable	Max Altitude	Operating: -15.2 to 3048 m (-50 to 10,000 ft) Storage: -15.2 to 10,668 m (-50 to 35,000 ft)
Communication			
Network Controller	Integrated 10M/100M/1000M Gigabit Ethernet ⁵		
Wi-Fi / Bluetooth ³	Intel® Centrino® Wireless-N 105 (Canyon Peak) Intel® Centrino® Wireless-N 2230 (Jackson Peak)		

Lenovo reserves the right to alter product offerings and specifications at any time without notice.
Nothing herein should be construed as constituting an additional warranty. Lenovo shall not be liable for technical or editorial errors or omissions contained herein.

ThinkCentre

lenovo FOR
THOSE WHO DO.

THINKCENTRE

Edge62z

TECHSPECS



Footnote 5: The term "10/100/1000" or "Gigabit" Ethernet indicates compliance with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

Footnote 3: Optional
Footnote 4: Quick MTM only

Footnote 6 : With Frame Stand
Footnote 7 : Various by optional features
 (webcam, ODD, etc.)

Lenovo reserves the right to alter product offerings and specifications at any time without notice.
Nothing herein should be construed as constituting an additional warranty. Lenovo shall not be liable for technical or editorial errors or omissions contained herein.